



Maintenance Guide

Luxury Vinyl Tile (LVT)

How to Maintain your flooring

CLICK

Luxury Vinyl (LVT) - Click

There are two basic maintenance options on LVT Flooring:

Domestic maintenance

The floor should be swept or vacuumed on a regular basis. Dirt spots and liquids should be cleaned up as soon as possible with water. For a completely clean, use a PU cleaner with a damp mop with a neutral detergent followed by rinsing with clean water.

Commercial Maintenance

The above can also be used but for larger areas, a spray and buffing can be used.

After an initial clean apply two light coats of a high-quality commercial floor finish. The floor can then be spray buffed using a polishing machine at low settings.

Preventative measures

Use protective entrance mats to help remove dirt and grime and reduce the risk of soiling.

Avoid use of rubber or latex-backed mats and furniture bases/feet. Install floor protectors to the bottom of furniture, such as felt pads, to help reduce the risk of scratching or marking.

Please note:

The following only applies to our Spectra range: Direct sunlight can discolour and even warp vinyl flooring.

Avoid direct sunlight and sunrooms with the use of blinds, curtains or sheer curtains to protect your floor.

As LVT has a maximum recommended surface temperature of 27°C, it's important to ensure this is not exceeded. If the area cannot be shaded with blinds, curtains or film-protected glass then glue down LVT should be selected in combination with a high temperature (HT) adhesive.

Luxury Vinyl (LVT) - Glue Down

There are two basic maintenance options on Luxury Glue Down Vinyl Flooring:

Domestic maintenance

The floor should be swept or vacuumed on a regular basis. Dirt, spots, and liquids should be handled with care and cleaned up as soon as possible with a damp cloth. For a completely clean, use a damp mop with a PH-neutral detergent, followed by a clean, damp cloth. Do not use unsuitable cleaners as the use of an incorrect cleaner can make the surface slippery and attract dirt.

Commercial maintenance

The above can also be applied to commercial settings. Spray cleaning and buffing with a PU refresher can also be used to achieve a full clean.

Preventative measures

Use protective entrance mats to help remove dirt and grime and reduce the risk of soiling.

Avoid the use of rubber or latex-backed mats and furniture bases/feet. Install floor protectors to the bottom of furniture, such as felt pads, to help reduce the risk of scratching or marking.

Prevent the floor from encountering water for the first 72 hours after installation so the adhesive bonding strength will not be affected.